

Customer Centers | United States  
 Electronics Manufacturing

Search | Contact us

3M™ Silicone Lubricant, 24 oz, 12 per case

## MSDS (United States)

Product search  
 Search by...

- 3M Electronics Manufacturing
- 3M™ Electronic Specialty Markets
- 3M™ Adhesives, Cleaners & Compounds
- 3M™ Adhesives, Cleaners & Compounds, Lubricants, Coatings & Sealers
- 3M™ Silicone Lubricant

3M™ Silicone Lubricant, 24 oz, 12 per case  
[Learn more...](#)

MSDS (United States)

MATERIAL SAFETY DATA SHEET  
 3M  
 3M Center  
 St. Paul, Minnesota  
 55144-1000  
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 1999, Minnesota Mining and Manufacturing Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that:

- 1) the information is copied in full with no changes unless prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

DIVISION: ADHESIVES DIVISION  
 TRADE NAME:  
 3M Brand Silicone Lubricant  
 ID NUMBER/U.P.C.:  
 62-4678-0930-7 00-21200-31321-9 62-4678-0931-5 - - -  
 62-4678-4930-3 00-21200-85822-2 62-4678-4935-2 - - -  
 78-8033-2219-3 - - -  
 ISSUED: November 02, 1999  
 SUPERSEDES: October 22, 1998  
 DOCUMENT: 05-6937-6

1. INGREDIENT	C.A.S. NO.	PERCENT
ISOBUTANE.....	75-28-5	70 - 80
HEPTANE.....	142-82-5	15 - 25
POLY (DIMETHYLSILOXANE).....	63148-62-9	3 - 7

IN CASE OF EMERGENCY: THE NUMBERS AT THE TOP OF THIS PAGE PROVIDE 24 HOUR RESPONSE FROM ANY PHONE FOR ALL EMERGENCIES WITH THIS PRODUCT. The components of this product are in compliance with the chemical notification requirements of TSCA. All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

2. PHYSICAL DATA

BOILING POINT:..... Compressed gas  
 VAPOR PRESSURE:..... Compressed gas  
 VAPOR DENSITY:..... 2.97 Air=1  
 EVAPORATION RATE:..... 1.90 Water=1  
 SOLUBILITY IN WATER:..... nil  
 SPECIFIC GRAVITY:..... 0.640 Water=1  
 PERCENT VOLATILE:..... ca. 95 % by wt  
 pH:..... N/A  
 VISCOSITY:..... N/A  
 MELTING POINT:..... N/D

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximate  
 MSDS: 3M Brand Silicone Lubricant  
 November 02, 1999

2. PHYSICAL DATA (continued) PAGE

-----  
APPEARANCE AND ODOR:

Liquid, in aerosol, transparent, very slight odor

-----  
3. FIRE AND EXPLOSION HAZARD DATA  
-----

FLASH POINT:..... -50.00 F TCC

Propellant

FLAMMABLE LIMITS - LEL:..... ca. 1.5 % by vol

FLAMMABLE LIMITS - UEL:..... ca. 8 % by vol

AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:

Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 4 REACTIVITY: 0 AEROSOL STORAGE: 3  
UNUSUAL REACTION HAZARD: none

-----  
4. REACTIVITY DATA  
-----

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

Heat.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Toxic Vapors, Gases or Particulates.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximate

□

MSDS: 3M Brand Silicone Lubricant

November 02, 1999

PAGE

-----  
5. ENVIRONMENTAL INFORMATION  
-----

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Ventilate area. Extinguish all ignition sources. Cover with absorbent material. Collect using non-sparking tools. Place in a U.S. DOT-approved container.

RECOMMENDED DISPOSAL:

Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. Facility must be capable of handling aerosol cans. Dispose of empty cans in a sanitary landfill. Dispose of waste product in a facility permitted to accept chemical waste.

RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: ca. 95 % South Coast Air Quality Mgmt Dist Method.  
Volatile Organic Compounds: ca. 565 gms/liter calculated per SCAQMD rule 443.1.  
Volatile Organic Compounds: 4.72 lb/gal.  
VOC Less H2O & Exempt Solvents: ca. 565 gms/liter calculated per SCAQMD rule 443.1.  
Hazardous Air Pollutants: 0 % by wt calculated.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = D001 (Ignitable)

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: Yes REACTIVITY: No ACUTE: Yes CHRONIC: Yes

-----  
6. SUGGESTED FIRST AID  
-----

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximate

□

MSDS: 3M Brand Silicone Lubricant  
November 02, 1999

PAGE

-----  
6. SUGGESTED FIRST AID (continued)  
-----

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

-----  
7. PRECAUTIONARY INFORMATION  
-----

EYE PROTECTION:

Avoid eye contact with vapor, spray, or mist. Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: butyl rubber, neoprene, nitrile rubber.

RECOMMENDED VENTILATION:

Do not use in a confined area or areas with little or no air movement. If exhaust ventilation is not adequate, use appropriate respiratory protection. Provide ventilation adequate to control vapor concentrations below recommended exposure limits and/or control spray or mist.

RESPIRATORY PROTECTION:

Avoid breathing of vapors, mists or spray. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Store at temperatures below 120 degrees F (49 degrees C). Store out

of direct sunlight. Keep out of the reach of children.

**FIRE AND EXPLOSION AVOIDANCE:**

Aerosol container contains flammable gas under pressure. Keep away from heat, sparks, open flame, and other sources of ignition. Extremely flammable liquid and vapor. Do not pierce or burn container, even after use. No smoking while handling this material. Avoid static discharge.

-----  
 Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximatel  
 □  
 MSDS: 3M Brand Silicone Lubricant  
 November 02, 1999 PAGE

-----  
**7. PRECAUTIONARY INFORMATION (continued)**  
 -----

EXPOSURE LIMITS					
INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN
ISOBUTANE.....	NONE	NONE	NONE	NONE	NONE
HEPTANE.....	400	PPM	TWA	ACGIH	
HEPTANE.....	500	PPM	STEL	ACGIH	
HEPTANE.....	400	PPM	TWA	OSHA	
HEPTANE.....	500	PPM	STEL	OSHA	
POLY(DIMETHYLSILOXANE).....	NONE	NONE	NONE	NONE	NONE

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

**SOURCE OF EXPOSURE LIMIT DATA:**

- ACGIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration
- NONE: None Established

-----  
**8. HEALTH HAZARD DATA**  
 -----

**EYE CONTACT:**

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

**SKIN CONTACT:**

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

During application:

Frostbite: signs/symptoms can include firm blanched areas, redness, pain, tissue destruction, swelling and scar tissue formation.

**INHALATION:**

Intentional concentration and inhalation may be harmful or fatal.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

-----  
 Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximatel  
 □  
 MSDS: 3M Brand Silicone Lubricant  
 November 02, 1999 PAGE

8. HEALTH HAZARD DATA (continued)

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

SECTION CHANGE DATES

INGREDIENTS	SECTION CHANGED SINCE October 22, 1998	ISSUE
PHYSICAL DATA	SECTION CHANGED SINCE October 22, 1998	ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximatel

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

□

< [Return to 3M™ Silicone Lubricant, 24 oz, 12 per case](#)

3M U.S. ^ Electronics Manufacturing

Visit other Customer Centers

Go >

Copyright 3M 1999-2000 | [Legal information](#) | [Privacy policy](#)