

MATERIAL SAFETY DATA SHEET

Date Printed: 06/20/2006

Date Updated: 02/05/2006

Version 1.6

Section 1 - Product and Company Information

Product Name N,N,N',N'-TETRAMETHYLETHYLENEDIAMINE,
REAGENTPLUS, 99%

Product Number T22500

Brand SIAL

Company Sigma-Aldrich

Address 3050 Spruce Street
SAINT LOUIS MO 63103 US

Technical Phone: 800-325-5832

Fax: 800-325-5052

Emergency Phone: 314-776-6555

Section 2 - Composition/Information on Ingredient

Substance Name	CAS #	SARA 313
N,N,N',N'-TETRAMETHYLETHYLENEDIAMINE	110-18-9	No

Formula C6H16N2

Synonyms 1,2-Bis-(dimethylamino)ethane *
1,2-Ethanediamine, N,N,N',N'-tetramethyl- (9CI) *
Propamine D * Temed * Tetrameen *
N,N,N',N'-Tetramethyl-1,2-diaminoethane *
N,N,N',N'-Tetramethylethanediamine *
N,N,N',N'-Tetramethyl-1,2-ethanediamine *
Tetramethyl ethylene diamine *
N,N,N',N'-Tetramethylethylenediamine * TMEDA

RTECS Number: KV7175000

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Flammable (USA) Highly Flammable (EU). Corrosive.
Harmful by inhalation and if swallowed. Causes burns.

HMIS RATING

HEALTH: 3
FLAMMABILITY: 3
REACTIVITY: 0

NFPA RATING

HEALTH: 3
FLAMMABILITY: 3
REACTIVITY: 0

For additional information on toxicity, please refer to Section 11.

Section 4 - First Aid Measures

ORAL EXPOSURE

If swallowed, wash out mouth with water provided person is

conscious. Call a physician immediately. Do not induce vomiting.

INHALATION EXPOSURE

If inhaled, remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen.

DERMAL EXPOSURE

In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician.

EYE EXPOSURE

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

Section 5 - Fire Fighting Measures

FLAMMABLE HAZARDS

Flammable Hazards: Yes

EXPLOSION HAZARDS

Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions.

FLASH POINT

68 °F 20 °C Method: closed cup

EXPLOSION LIMITS

Lower: 0.98 % Upper: 9.08 %

AUTOIGNITION TEMP

N/A

FLAMMABILITY

N/A

EXTINGUISHING MEDIA

Suitable: For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

FIREFIGHTING

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable liquid. Emits toxic fumes under fire conditions.

Section 6 - Accidental Release Measures

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL

Evacuate area. Shut off all sources of ignition. Use nonsparking tools.

PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear self-contained breathing apparatus, rubber boots, and heavy rubber gloves.

METHODS FOR CLEANING UP

Cover with dry-lime, sand, or soda ash. Place in covered containers using non-sparking tools and transport outdoors. Ventilate area and wash spill site after material pickup is complete.

Section 7 - Handling and Storage

HANDLING

User Exposure: Do not breathe vapor. Do not get in eyes, on skin, on clothing. Avoid prolonged or repeated exposure.

STORAGE

Suitable: Keep tightly closed. Keep away from heat, sparks, and open flame.

SPECIAL REQUIREMENTS

Handle and store under inert gas. Air and moisture sensitive.

Section 8 - Exposure Controls / PPE

ENGINEERING CONTROLS

Safety shower and eye bath. Use nonsparking tools. Use only in a chemical fume hood.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory: Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator.
Hand: Compatible chemical-resistant gloves.
Eye: Chemical safety goggles.
Other: Faceshield (8-inch minimum).

GENERAL HYGIENE MEASURES

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

Section 9 - Physical/Chemical Properties

Appearance	Physical State: Clear liquid Color: Colorless	
Property	Value	At Temperature or Pressure
Molecular Weight	116.21 AMU	
pH	N/A	
BP/BP Range	120.0 - 122.0 °C	760 mmHg
MP/MP Range	- 55.0 °C	
Freezing Point	N/A	
Vapor Pressure	N/A	
Vapor Density	N/A	
Saturated Vapor Conc.	N/A	
SG/Density	0.775 g/cm ³	
Bulk Density	N/A	
Odor Threshold	N/A	
Volatile%	N/A	
VOC Content	N/A	
Water Content	N/A	
Solvent Content	N/A	

Evaporation Rate	N/A	
Viscosity	N/A	
Surface Tension	N/A	
Partition Coefficient	Log Kow: 0.3	
Decomposition Temp.	N/A	
Flash Point	68 °F 20 °C	Method: closed cup
Explosion Limits	Lower: 0.98 % Upper: 9.08 %	
Flammability	N/A	
Autoignition Temp	N/A	
Refractive Index	1.4179	
Optical Rotation	N/A	
Miscellaneous Data	N/A	
Solubility	Solubility in Water:10 mg/ml H2O, 20°C complete, colorless Other Solvents: MOSTORGANIC SOLVENTS	

N/A = not available

Section 10 - Stability and Reactivity

STABILITY

Stable: Stable.

Conditions of Instability: May discolor on exposure to air and moisture.

Materials to Avoid: Strong oxidizing agents Carbon dioxide.
Copper, Copper alloys

HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and nitrogen oxides.

HAZARDOUS POLYMERIZATION

Hazardous Polymerization: Will not occur

Section 11 - Toxicological Information

ROUTE OF EXPOSURE

Skin Contact: Causes burns.

Skin Absorption: May be harmful if absorbed through the skin.

Eye Contact: Causes burns.

Inhalation: Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. May be harmful if inhaled. Harmful if inhaled.

Ingestion: Harmful if swallowed.

SIGNS AND SYMPTOMS OF EXPOSURE

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin.

Inhalation may result in spasm, inflammation and edema of the larynx and bronchi, chemical pneumonitis, and pulmonary edema.

TOXICITY DATA

Oral

Rat

268 mg/kg

LD50

Remarks: Spinal Cord:Other degenerative changes. Brain and Coverings:Other degenerative changes.

Inhalation

Rat
1,318 ppm
LC50
Remarks: Behavioral:Ataxia. Sense Organs and Special Senses
(Nose, Eye, Ear, and Taste):Eye:Other. Behavioral:Irritability.

Oral
Mouse
630 mg/kg
LD50

Skin
Rabbit
5390 mg/kg
LD50

Subcutaneous
Rabbit
1230 MG/KG
LD50

Oral
Quail
> 316 mg/kg
LD50

IRRITATION DATA

Skin
Rabbit
10 mg
24H
Remarks: Open irritation test

Eyes
Rabbit
0.75 mg
Remarks: Severe irritation effect

Section 12 - Ecological Information

Section 13 - Disposal Considerations

APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Section 14 - Transport Information

DOT

Proper Shipping Name: Flammable liquid, toxic,
corrosive, n.o.s.
UN#: 3286
Class: 3
Packing Group: Packing Group II
Hazard Label: Flammable liquid
Hazard Label: Toxic substances.
Hazard Label: Corrosive

PIH: Not PIH

IATA

Proper Shipping Name: 1,2-DI-(DIMETHYLAMINO) ETHANE
IATA UN Number: 2372
Hazard Class: 3
Packing Group: II

Section 15 - Regulatory Information

EU DIRECTIVES CLASSIFICATION

Symbol of Danger: F-C
Indication of Danger: Highly Flammable. Corrosive.
R: 11-20/22-34
Risk Statements: Highly flammable. Harmful by inhalation and if swallowed. Causes burns.
S: 16-26-36/37/39-45
Safety Statements: Keep away from sources of ignition - no smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

US CLASSIFICATION AND LABEL TEXT

Indication of Danger: Flammable (USA) Highly Flammable (EU). Corrosive.
Risk Statements: Harmful by inhalation and if swallowed. Causes burns.
Safety Statements: Keep away from sources of ignition - no smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

UNITED STATES REGULATORY INFORMATION

SARA LISTED: No
TSCA INVENTORY ITEM: Yes

CANADA REGULATORY INFORMATION

WHMIS Classification: This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by the CPR.
DSL: Yes
NDSL: No

Section 16 - Other Information

DISCLAIMER

For R&D use only. Not for drug, household or other uses.

WARRANTY

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Inc., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2006 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.